

LOW VOLTAGE AND HIGH VOLTAGE TECHNICAL SPECIFICATION

Electrical

| |
|---|
| Input voltage: Low Voltage = 100-120V, High Voltage = 200-240V |
| Frequency: Low Voltage = 50 or 60Hz, subject to voltage (100-110V at 50-60Hz; 120V at 60Hz); High Voltage = 50-60Hz |
| Rated power: 100-110V at 1150 W; 120V at 1400W; 200-240V at 1600W |
| Motor type: Dyson digital motor V4 – brushless DC Motor |
| Motor switching rate: 6,100 per second |
| Motor speed: 92,000rpm |
| Amp: Recommended dedicated 15 amp circuit, Low voltage = 10.81 amps at 120V, High voltage = 7.50 amps at 220V |
| Operating temperature range: 32°– 104°F |
| Heater type: None |
| Standby power consumption: Less than 0.5W |

Construction

| |
|---|
| Casing construction: Polycarbonate-ABS casing |
| Antimicrobial coating type: Antimicrobial molded additive in fascia and blades can help prevent the growth of bacteria. |
| Color finish: Gray or White |
| Light reflective value: 28.3 (gray) 77.4 (white) |
| Galvanized steel back plate/mounting bracket |
| Exterior screw type: Anti-tamper M6 machine screw |
| Water ingress protection to IP35 |

Filter

| |
|--|
| Sealed HEPA filter (glass fiber and fleece prelayer) |
| Removes 99.97% of particles, as small as 0.3 microns |

Operation

| |
|--|
| Touch-free infra-red activation |
| Hand dry time measurement: 10-12 seconds* |
| Operation lock-out period: 30 seconds |
| Airspeed at apertures: 430mph |
| Maximum Altitude: 2,000 meters/6,561 feet |
| Operating airflow: Up to 7.93 gallons/sec (30 liters/sec) and 63.6 CFM |
| Rated operating noise power: 81 db(A) |

Logistics

| |
|--|
| Serial number prefix: Gray FT6; White FT7 |
| Net weight: 17.88lb / 8.11 kg |
| Packaged weight: 24.58lb / 11.15 kg |
| Packaged dimensions: H28 ⁵ / ₁₆ " (735mm) × W14 ¹ / ₈ " (359mm) × D12" (304mm) |
| UPC barcodes: |
| Gray – Low Voltage: 885609001050, High Voltage: 885609004440; |
| White – Low Voltage: 885609001067, High Voltage: 885609004433 |

Standard warranty

| |
|--|
| 5 year parts and 1 year limited labor warranty |
|--|

Accreditations

| |
|-----------------------------------|
| Carbon Trust |
| HACCP International |
| NSF International P335 |
| ADA compliant |
| Contributes to LEED certification |



Product range (Select one)

AB14 Gray

| |
|--|
| Part number/SKU |
| <input type="checkbox"/> Low Voltage: 301853-01 |
| <input type="checkbox"/> High Voltage: 304663-01 |



AB14 White

| |
|--|
| Part number/SKU |
| <input type="checkbox"/> Low Voltage: 301854-01 |
| <input type="checkbox"/> High Voltage: 304664-01 |



The Carbon Reduction Label is the registered trademark of the Carbon Trust. HACCP International non-food certification mark is the registered trademark of HACCP International. HACCP International have certified Dyson products based on their recommended installation and operating conditions. The NSF logo is the registered trademark of NSF International.

*Dry time determined using Dyson test method 769 based on NSF P335 to a measurement of 0.1g residual moisture.

For more information, please contact Dyson:


1-888-397-6622 | airbladeinfo@dyson.com | www.dyson.com




TECHNICAL SPECIFICATION

AB
14

REAR ELEVATION



SIDE ELEVATION



All dimensions shown in inches (+/- 3/16") and in millimeters (+/- 5mm)



| Recommended installation heights from floor | | | |
|---|--------------------|-------------------|-------------------|
| Male | X 41 3/8" (1050mm) | Y 39" (990mm) | Z 15 3/8" (390mm) |
| Female | X 38 3/8" (975mm) | Y 36" (915mm) | Z 12 3/8" (315mm) |
| Child or disabled | X 34 1/2" (875mm) | Y 32 1/8" (815mm) | Z 8 1/2" (215mm) |
| Machine dimensions | | | |
| Height 26" (661mm) × Width 11 7/8" (303mm) × Depth 9 3/4" (247mm) | | | |

| Minimum clearance | |
|---|-----------------|
| 7 7/8" (200mm) from floor; 2" (50mm) clearance either side and above machine. | |
| Cable entry point from floor | |
| Male | 28 1/2" (725mm) |
| Female | 25 5/8" (650mm) |
| Child or disabled | 21 5/8" (550mm) |