dyson airblade V

TECHNICAL SPECIFICATION





REAR ELEVATION SIDE ELEVATION 234 100 190 Fixing Rear cable locations entry point (4)Side cable Side cable entry point entry point Fixing locations -(4) Ζ See table for recommended mounting heights

FLOOR

Recommended installation heights from floor						
Male	Х	1324 mm	Υ	1300 mm	Z	930 mm
Female	Χ	1289 mm	Υ	1265 mm	Z	895 mm
Child or disabled	Х	1074 mm	Υ	1050 mm	Z	680 mm
Child 5-8	Χ	952 mm	Υ	928 mm	Z	558 mm
Child 8-11	Х	1052 mm	Υ	1028 mm	Z	658 mm
Child 11-14	Χ	1132 mm	Υ	1108 mm	Z	738 mm
Machine dimensions						
Height 394 mm Width 234 mm Depth 100 mm						

Minimum clearance 220mm clearance either side and 30mm above machine.					
Male	1089 mm				
Female	1054 mm				
Child or disabled	839 mm				
Child 5-8	717 mm				
Child 8-11	817 mm				
Child 11-14	897 mm				

All dimensions shown in mm (+/-5 mm)

dyson airblade V



Electrical

Input voltage/Frequency: 200-240 V 50&60 Hz Standby power consumption: Less then 0.5 W

Motor specification: 1,000 W digital brushless motor

Heater type: None

Construction

Fascia: Polycarbonate

Antibacterial coating type:

HU02 (Sprayed Nickel) contains antibacterial additive in paint.

HU02 (White) contains antibacterial moulded additive.

Can help prevent the growth of bacteria.

Back plate mounting bracket: ABS/PBT Plastic Exterior screw type: Anti-tamper 4 mm Pin-Hex

Water ingress protection to IP24

Filter

HEPA filter (Glass fibre and fleece prelayer)

99.9% of particles captured

Operation

Touch free capacitive sensor activation

Hand dry time measurement: 12 seconds (Measurement based on NSF Protocol P.335)

Sound power level: 79 dB(A)

Sound pressure level @ 2 m: 63 dB(A)1

Operation lock-out period: 30 seconds Airspeed at aperture: 690 km/h / 430 mph

Maximum altitude: 2,000 metres / 6,561 ft.

Logistics

Single unit order code:

Malaysia: Sprayed Nickel 307735-01, White 307734-01 South Korea: Sprayed Nickel 307596-01, White 307595-01 Rest of world: Sprayed Nickel 307170-01, White 307169-01

Unit barcode:

Malaysia: Sprayed Nickel 5025155025871, White 5025155025864 South Korea: Sprayed Nickel 5025155025833, White 5025155025826 Rest of world: Sprayed Nickel 5025155025796, White 5025155025710

Net weight: 2.9 kg / 6.17 lbs

Packaged weight: 4.0 kg / 8.81 lbs

Packaged dimensions:

 $(H)145 \times (W)455 \times (D)274 \text{ mm} / (H)5^{3}/_{4}" \times (W)17^{7}/_{8}" \times (D)10^{3}/_{4}"$

Standard guarantee

5 year guarantee

¹Sound pressure measured at 2 m distance, in a semi-anechoic chamber.







The NSF logo is the registered trademark of NSF International.

Quiet Mark is a registered trademark of the Noise Abatement Society.



Product range

Sprayed Nickel





