
UPPERCUT

The Fastest Way to Start Saving Water!





Bedpan Washer Dual Flush Flushometer

Description

Exposed Bedpan Washer Water Closet Flushometer with Dual Flush Feature, for floor mounted or wall hung top spud bowls.

Flush Cycle

Model WES BPW-1000-1.6/1.1 High Efficiency (DOWN - 1.6 gpf/ 6.0 Lpf, UP - 1.1 gpf/ 4.2 Lpf)

Specifications

Dual Flush, Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

- Lifting Handle UP initiates reduced flush (1.1 gpf/4.2 Lpf), eliminating liquid and paper waster, saving a ½-gallon of water
- Pushing Handle DOWN initiates full flush (1.6 gpf/6.0 Lpf), eliminating all waste
- Reduces water volume by up to 30% when activated UPWARDS
- PERMEX[®] Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
 Antimicrobial Coating on Handle Protects Against Germs
- Distinctive Green ADA Compliant Metal Non-Hold-Open Handle with Triple Seal Handle Packing signifies Water Conserving Device
- Packing signifies Water Conserving Device • 1" I.P.S. Screwdriver Bak-Chek[®] Angle Stop
- Vandal Resistant Stop Cap
- Adjustable Tailpiece
- Vacuum Breaker with Flush Connection
- Spud Coupling and Spud Flange for 1½" Top Spud
- Spud Coupling and Spud Flange for 1/2 Top Spud
 Sweat Solder Adapter with Cover Tube and Cast Wall Flange
- Sweat Solder Adapter with Cover rube and Cast wait Flange
 High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID Technology
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker Molded from PERMEX[®] Rubber Compound for Chloramine Resistance

• Includes two (2) adhesive backed Metal Wall Plates etched with instructions

- Bedpan Washer Diverter Assembly with the following features:
- Solid One-piece Body Construction
- Solid Brass Spray Arm
- Counter Balanced Pivot Assembly
- Diverter Valve Wall Support

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037. Installation meets ADA height requirements.

Variations

YO Bumper on Angle Stop (for open front seat without cover)

Accessories

See Accessories Section of the Bedpan Washer catalog for details on these and other Flushometer variations.



This appear for Architact/Engineer approval	
This space for Architect/Engineer approval	
Job Name	Date
Model Specified	Quantity
Variations Specified	
Customer/Wholesaler	
Contractor	
Architect	

The information contained in this document is subject to change without notice.



WES BPW 1000 09-13 Copyright © 2013 SLOAN VALVE COMPANY

Two Wall Bumpers (for open front seat without cover)