


© Copyright 1997 SLOAN VALVE COMPANY Printed in U.S.A.

Hydraulic Royal[®] Prison Model Flushometer



Description

Concealed Hydraulically Operated Urinal Flushometer, for 11/2" back inlet urinals.

Flush Cycle

□ Model 9609 Conventional (3.5 gpf/13.2 Lpf) □ Model 9609-1.5 Water Saver (1.5 gpf/5.7 Lpf) □ Model 9609-1 Low Consumption (1.0 gpf/3.8 Lpf)

Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Urinal Flushometer for either left or right hand supply with the following features:

- Dual Filtered By-Pass
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker to be molded from PERMEX[™] rubber compound for Chloramine resistance
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Wheel Handle Bak-Chek™ Angle Stop
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker
- Elbow Flush Connection
- Coupling for 1¹/₂" NPT Back Inlet Urinals (for connection in the pipe chase - flush connection through the wall not provided by Sloan)
- Sweat Solder Adapter
- Exposed parts Chrome Plated

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

Actuator Types: (please check one)

MBFW Metal Button Fixture Wall Actuator (HY-100-A) (rear access)

MBPM Metal Button Panel Mount (HY-108-A) for use only with Wall Box

See Actuator Section of the Sloan catalog for details on Actuators.

Variations

R

51

U 11/4" Flush Connection

 Prison Flushometers can also be provided in Regal[®] Models. All rough-in dimensions remain the same.

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.





Made in the U.S.A.

This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 PHONE: 1-800 982-5839 • FAX: 1-800 447-8329 • http://www.sloanvalve.com