

MECHANICAL FAUCETS

1100-GN8AE3VPCABCP

Manual Faucets



Product Type

Deck Mounted 8" Fixed Centers Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 2.2 GPM (8.3 L/min) Vandal Proof Aerator
- 2" Vandal Proof Canopy Single Wing
- Quatern
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- ECAST® design provides durable construction with total lead content equal to or less than 0.25% by weighted average
- CFNow! Item Ships in 3 Days

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



ECAST

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.



Manual Faucets



Technical drawings of a riser assembly, showing side and front views with dimensions in inches and millimeters.

Side View Dimensions:

- Top horizontal distance: 2" [51mm]
- Top horizontal distance: 10" [254mm]
- Top horizontal distance: 1" DIA. [24mm]
- Top horizontal distance: 1-3/4" DIA. [44mm]
- Top horizontal distance: 1/2" NPSM COUPLING NUT FOR 3/8" OR 1/2" FLEXIBLE RISER
- Top horizontal distance: 4" [102mm]
- Top horizontal distance: 8" [203mm]
- Top horizontal distance: 7-3/4" [197mm]
- Top horizontal distance: 8" [203mm]
- Top horizontal distance: 13-1/2" [343mm]
- Top horizontal distance: 2" [51mm]
- Top horizontal distance: 1-1/16" - 1-1/2" [2mm - 38mm] WARE THICKNESS
- Top horizontal distance: 3"

Front View Dimensions:

- Top horizontal distance: 2-3/8" [60mm]
- Top horizontal distance: 10" [254mm]
- Top horizontal distance: 1" DIA. [24mm]
- Top horizontal distance: 1-3/4" DIA. [44mm]
- Top horizontal distance: 1/2" NPSM COUPLING NUT FOR 3/8" OR 1/2" FLEXIBLE RISER
- Top horizontal distance: 4" [102mm]
- Top horizontal distance: 8" [203mm]
- Top horizontal distance: 7-3/4" [197mm]
- Top horizontal distance: 8" [203mm]
- Top horizontal distance: 13-1/2" [343mm]
- Top horizontal distance: 2" [51mm]
- Top horizontal distance: 1-1/16" - 1-1/2" [2mm - 38mm] WARE THICKNESS
- Top horizontal distance: 3"

Last Revision: 07/15/2016 • Date Printed: 12/13/2017 • Product specifications subject to change without notice