

MECHANICAL FAUCETS

786-TWGN2AE3XKABCP

Manual Faucets



Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet with Third Water Inlet

Features & Specifications

- 8" Fixed Centers
- 2.2 GPM (8.3 L/min) Aerator
- 4" Vandal Proof Wristblade
- Ceramic
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- 3/8" NPT Female Third Water Inlet
- ECAST® design provides durable construction with total lead content equal to or less than 0.25% by weighted average
- CFNow! Item Ships in 3 Days

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown

☐ Submitted with Variations

Date _____



ECAST

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.



Manual Faucets



Technical drawing of a three-way water meter assembly, showing three views: a side view, a top view, and a front view.

Dimensions (inches):

- Side View:
 - Horizontal distance from left to center: 4 [102]
 - Horizontal distance from center to right: 4 [102]
 - Horizontal distance from left to right: 8 [203]
 - Vertical distance from base to top of meter: 7-1/2 [191]
 - Vertical distance from base to top of riser: 11-5/8 [295]
 - Vertical distance from base to top of riser (excluding meter): 4-3/8 [111]
- Top View:
 - Horizontal distance from left to center: 4 [102]
 - Horizontal distance from center to right: 4 [102]
 - Horizontal distance from left to right: 8 [203]
- Front View:
 - Horizontal distance from left to center: 4 [102]
 - Horizontal distance from center to right: 4 [102]
 - Horizontal distance from left to right: 8 [203]

Labels:

- Ø 1-1/4 [32]
- Ø 1-1/8 [29]
- Ø 2-1/4 [57]
- 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER
- 3/8 NPT FEMALE THIRD WATER CONN. FURNISHED LOOSE
- 1-3/8 [35] MAXIMUM WARE THICKNESS
- 3°
- 5-3/8 [137]

Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com