

MECHANICAL FAUCETS

930-VRCP

Water Faucets



Product Type

Deck Mounted Single Hole Vandal Proof Hot and Cold Water Mixing Faucet with Vacuum Breaker

Features & Specifications

- Single Hole
- 6" Rigid Gooseneck Spout with Atmospheric Vacuum Breaker
- Full Flow Nozzle
- 2-1/2" Vandal Proof Cross Handles
- Slow Compression Operating Cartridges
- 3/8" Compression Flexible Stainless Steel Supply Hoses
- Atmospheric Vacuum Breaker, Not Intended for Continuous Pressure Applications
- All Threaded Connections Factory Assembled
- Anti-Rotational Body Deck Pin to Prevent Turning
- Atmospheric Vacuum Breaker, Not Intended for Continuous Pressure Applications

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com

Water Faucets



PRIMARY PIN LOCATION

23/32 [18]

$\phi 1-1/8$ [29]

$\phi 1/4$ [6] — OPTIONAL HOLE LOCATION, ADDITIONAL PIN REQUIRED

PLAN VIEW HOLE LOCATION FOR BODY SHANK AND PIN

18-7/8 [479]

16-3/4 [425]

7-3/8 [187]

$\phi 1-1/16$ [27]

13-1/4 [337]

6-1/8 [156]

3°

7 [178]

$\phi 2$ [51]

1/4 [6] PIN LENGTH X $\phi 3/16$ [5]

1/8-1-5/8 [3-41] WARE THICKNESS

3/8 COMPRESSION THREAD

Operation and Maintenance



Last Revision: 07/15/2016 • Date Printed: 12/4/2018 • Product specifications subject to change without notice