ACCESSORIES AND PARTS E24JKCP



Product Type

In-Line Atmospheric Vacuum Breaker

Features & Specifications

- Vacuum Breakers for Hand Showers are used for noncontinuous pressure, health hazard, applications and are backsiphonage backflow preventers.
- 125 PSI Maximum Working Pressure
- 140°F (60°C) Maximum Temperature
- ASSE 1014 Compliant
- This device should only be used in areas where spillage of water will not cause damage.
- This device is not to be used under continuous pressure or where there is a possibility that a back pressure condition may develop.
- Atmospheric Vacuum Breaker, Not Intended for Continuous Pressure Applications

Job Name	
Item Number	
Section/Tag	
Model Specified	
Architect	
Engineer	
Contractor	
[] Submitted as Shown	[] Submitted with Variations
Date	



E24JKCP



Architect/Engineer Specification

Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

