

Product Type

Wall Mounted Pressure Balancing Pressure Balancing Tub and Shower Valve with Shower Head

Features & Specifications

- Pressure Balancing
- Pressure Balancing Tub and Shower Valve Only
- Vandal Proof Wall Mounted Institutional Shower Head
- Pressure Balancing Valve Cartridge
- 1/2" Nominal Copper and 1/2" NPT Hot and Cold Supply Inlets and Outlets
- Shower Valve Cycles from Cold to Hot
- Embossed and Color Coded Indexing on Wall Plate
- Integral Service Stops with Checks to Prevent Cross Flow
- Diverter Valve with Indexed Wall Flange Designed to Alternate between Shower Head and Hand Spray
- Wall Elbow with In-Line Vacuum Breaker
- 1.5 GPM Hand Spray with 69" Stainless Steel Hose and Pause Control (Wall Hook Included)
- Diverter Tub Spout

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-120°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- ASSE 1016
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Architect/Engineer Specification

1/2 NPT FEMALE THREAD (BACK SIDE)

2-1/8 [54]

2-3/4 [70]

1-3/8 [35]

25° OR 30° (ADJUSTABLE)

FINISHED WALL

Ø 3-1/2 [89]

1-1/2 [38] MIN.
2-1/4 [57] MAX.

Ø 6-3/4 [171]

1/2 NPT FEMALE THREAD

3-5/8 [92]

4-7/8 [124]

4 [102] APPROX.

RIM OF TUB

2-1/2 MIN. [64]

1/4-20 X 1 [25]

ALLEN HEAD SCREWS WITH ANCHORS (4 PLACES)

78 [198] APPROX. TO FINISHED FLOOR

1/2-NPT MALE THREAD OR 1/2 NOMINAL COPPER SWEAT (4 PLACES)

3-1/8 [79]

3-3/8 [86]

6-3/8 [162]

3-1/4 [83]

Ø 5-7/8 [149] ROUGH-IN GUIDE

1/2-NPT MALE THREAD OR 1/2 NOMINAL COPPER SWEAT (4 PLACES)

BACK VIEW OF VALVE ONLY

AS REQUIRED

AS REQUIRED TO SUIT

AS REQUIRED TO SUIT

1-3/8 [35]

FINISHED WALL

1/2 NPT FEMALE INLET

Ø 2-1/8 [54]

BACKFLOW PREVENTER

AS REQUIRED TO SUIT

Last Revision: 07/16/2018 • Date Printed: 08/29/2019 • Product specifications subject to change without notice