

Tub and Shower Fittings

Product Type

Wall Mounted Pressure Balancing Pressure Balancing Tub and Shower Valve with Shower Head

Features & Specifications

- Pressure Balancing
- Pressure Balancing Tub and Shower Valve Only
- 1.5 GPM Max. Flow Rate @ 80 PSI Shower Head
- Pressure Balancing Valve Cartridge
- 1/2" Nominal Copper and 1/2" NPT Hot and Cold Supply Inlets and Outlets
- Includes Shower Head Arm and Wall Flange
- Shower Valve Cycles from Cold to Hot
- Embossed and Color Coded Indexing on Wall Plate
- Integral Service Stops with Checks to Prevent Cross Flow
- Diverter Valve with Indexed Wall Flange Designed to Alternate between Shower Head and Hand Spray
- Wall Elbow with In-Line Vacuum Breaker
- 59" Stainless Steel Hose and 1.5 GPM Hand Spray with Pause Control
- 36" Wall Mounted ADA Grab Bar with Hand Spray Holder

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-120°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- ASSE 1016
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



Architect/Engineer Specification

Technical drawings of the back view of a valve assembly, showing various components and dimensions.

Left Side View:

- Top view shows a $\varnothing 2-1/2$ [64] FLANGE.
- Side view shows a $\varnothing 3-1/2$ [89] dimension.
- Bottom view shows a $\varnothing 6-3/4$ [171] dimension.
- Text: "ALL DOTTED LINE PIPING SUPPLIED BY OTHERS".
- Text: "TUB OUTLET TO BE PLUGGED (PLUG BY OTHERS)".

Right Side View:

- Top view shows a $\varnothing 3-1/8$ [79] dimension.
- Side view shows a $\varnothing 3-1/8$ [79] dimension.
- Bottom view shows a $\varnothing 3-1/8$ [79] dimension.
- Text: "BACKFLOW PREVENTER".
- Text: "AS REQUIRED TO SUIT".

Bottom View:

- Shows a $\varnothing 5-7/8$ [149] ROUGH-IN GUIDE.
- Text: "1/2-NPT MALE THREAD OR 1/2 NOMINAL COPPER SWEAT (4 PLACES)".
- Text: "3-1/4 [83]".
- Text: "6-3/8 [162]".
- Text: "1/2 [13]".
- Text: "1-1/2 [38] MIN. 2-1/4 [57] MAX.".
- Text: "78 [1981] APPROX. TO FINISHED FLOOR".
- Text: "1/2 NPT MALE THREAD".
- Text: "FINISHED WALL".
- Text: "9-1/4 [235]".
- Text: "3 [76]".
- Text: "3-1/8 [79]".
- Text: "3-3/8 [86]".
- Text: "1/2-NPT MALE THREAD OR 1/2 NOMINAL COPPER SWEAT (4 PLACES)".
- Text: "3-1/8 [79]".
- Text: "1/2 NPT FEMALE INLET".
- Text: "2-1/4 [57]".
- Text: "FINISHED WALL".
- Text: "36 [914]".
- Text: "AS REQUIRED".

BACK VIEW OF VALVE ONLY

Last Revision: 07/16/2018 • Date Printed: 09/4/2019 • Product specifications subject to change without notice