

#### **CODE NUMBER**

3366113

### **DESCRIPTION**

Sloan® XLERATOR® Sensor-Operated Wall - Surface Hand Dryer EHD-502-ECO, HEPA, 208/277V, Sloan® XLERATOR® Sensor-Operated Wall - Surface Hand Dryer.

#### **DETAILS**

Voltage: 208/277V
Wattage: 50/60Hz
Amperage: 2.0-2.2
Mounting: Wall - Surface
Power Type: Hardwired
Depth: 12 86/125" (322mm)
Height: 6 86/125" (170mm)
Width: 11 ¾" (298mm)

• Finish: Graphite (GR)


### **FEATURES**

- Automatically operates by means of an Infrared Optical Sensor with 35-second lockout feature, it activates a strong controlled air blast
- Residual moisture is evaporated with a warm stream of air up to 135°F/57°C
- One-piece heavy-duty rib reinforced die cast zinc alloy housing minimizes damage to dryer in abusive environments
- 95% cost savings vs. paper towels
- Can be easily positioned to comply with ADA requirements or for juvenile height
- Can install multiple units on one circuit
- HEPA filtration
- Available in Polished White, Matte White, Polished Chrome, Brushed Nickel and Graphite
- Hygienic hand dryer solution
- 10 second dry time
- Virtually maintenance free
- Available with HEPA Filtration System proven to remove 99.97% of potentially present bacteria at 0.3 microns from the air

### **DOWNLOADS**

- Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions
- Additional Downloads





# **COMPLIANCES & CERTIFICATIONS**













(BAA Compliant, cUL Certified, EPD, HEPA, Proposition 65, UL Certified)

## RECOMMENDED SPECIFICATION

Sloan Xlerator Sensor Operated Hand Dryer. 208V/230V Graphite Finish.

# NOTES

All information contained within this document subject to change without notice.