

CODE NUMBER

3982525

DESCRIPTION

1.0 gpf, Polished Chrome Finish, Top Spud, Single Flush, Battery, Regal® Exposed Sensor Urinal Flushometer.

DETAILS

Flush Volume: 1.0 gpf (3.8 Lpf)Finish: Polished Chrome (CP)

Power Type: BatteryBattery Life: 3 yearsValve: Diaphragm

• Valve Body Material: Semi-red Brass

• Fixture Type: Urinal

• Fixture Connection: Top Spud

• Rough-In Dimension: 11 ½" (292mm)

Spud Coupling: ³/₄" (19mm)
Supply Pipe: ³/₄" (19mm)

FEATURES

• Four (4) size C alkaline batteries included

• "Low Battery" Flashing LED

• "User in View" Flashing LED

• No External Volume Adjustment to Ensure Water Conservation

• True Mechanical Override Flush Button

• 72-Hour Sentinel Flush

 Sweat Solder Adapter w/Cover Tube and Cast Wall Flange with Set Screw

 Stop Seat and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine resistance

• 3/4" I.P.S. Screwdriver Bak-Chek® Angle Stop with stop plug



COMPLIANCES & CERTIFICATIONS







(ADA Compliant, UPC Certified, BAA Compliant)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

ELECTRICAL SPECIFICATIONS

• Battery Life: 3 years

VALVE OPERATING PRESSURE (FLOWING)

15-80 PSI (103-552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- EBV-500/550-A Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Regal Flushometers Repair and Maintenance Guide
- Additional Downloads

NOTES


All information contained within this document subject to change without notice.


Looking for other variations of the REGAL 186 SFSM product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.



ROUGH-IN





Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com