



Gem•2® Model Flushometer

137

Description

Exposed, Water Closet Flushometer for back inlet squat toilets.

Flush Cycle

- ☐ Model 137-1.6 Low Consumption (1.6 gpf/6.0 Lpf)
- ☐ Model 137-2.4 (2.4 gpf/9.0 Lpf)
- ☐ Model 137 Water Saver (3.5 gpf/13.2 Lpf)

Specifications

Quiet, Exposed, Piston Type, Chrome Plated Closet Flushometer with the following features:

- Fixed Volume Piston with Filtered O-ring Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Locking Vandal Resistant Stop Cap
- Adjustable Tailpiece
- Vacuum Breaker Flush Connection for 11/2" Back Inlet
- Wall Flange
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Handle Packing, Stop Seat and Vacuum Breaker Molded from PERMEX™ Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME A112.19.2.

Variations

	11/4" Flush Connection	
☐ XYV	Less Vacuum Breaker	
□ YB	Sweat Solder Adapter Kit	
☐ YBYC Sweat Solder Adapter & Cast Wall Flange with Set Screw		
□ YJ	Split Ring Pipe Support	
□ YK	Solid Ring Pipe Support	

Note: Bak Chek® Angle Stop available with 1" Whitworth Thread (please specify).

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.







This space for Architect/Engineer approval		
Job Name	Date	
Model Specified	Quantity	
Variations Specified		
Customer/Wholesaler		
Contractor		
Architect		

The information contained in this document is subject to change without notice.



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131 Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 Made in the U.S.A. www.sloanvalve.com