

# HAND DRYER COMPARISON

## XLERATOR®/XLERATOReco® VS. ThinAir® VS. Airblade V



COMPANY	EXCEL DRYER	EXCEL DRYER	DYSON
SERIES	XLERATOR	ThinAir	Airblade V
MODEL	XL-BW, W, GR, SP, SI, C, SB, SB-SI	TA-ABS, W, GR, SP, SI, SB, SB-SI	HU02
ONLINE PRICING	\$535 - \$1,110	\$395 - \$1,010	\$949



Smart EPD® verifies Environmental Product Declarations (EPDs) for consistency with the LCA and conformance with global Product Category Rules (PCR) for hand dryers. UL Environment published the first global PCR for hand dryers. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in Environmental Product Declarations, enabling specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.



PCR TESTED	Yes	Yes	No
DRY TIME <sup>1</sup>	8 sec	14 sec	12 sec
ENERGY PER USE <sup>1</sup>	3.7 Wh	3.7 Wh	N/A
EPD CERTIFIED	Yes	Yes	No
HPD CERTIFIED	Yes	Yes	No

COVER MATERIAL	Thermoset BMC-Composite, Zinc Die-Cast, Stainless Steel	Antimicrobial ABS, Stainless Steel, Painted Stainless Steel	Polycarbonate ABS Plastic
FINISH	White, Textured Graphite, Chrome, Custom Special Paint, Special Image, Brushed Stainless, Brushed Stainless Special Image	White ABS, White Painted, Graphite Textured Paint, Special Paint, Special Image, Brushed Stainless, Brushed Stainless Special Image	White, Sprayed Nickel
AMPS/VOLTS/WATTS	11.3 - 12.2 A / 110 - 120 V / 1240 - 1450 W 5.6 - 6.2 A / 208 - 277 V / 1160 - 1490 W 6.1 A / 230 V / 1410 W	7.0 - 7.8 A / 110 - 120 V / 750 - 920 W (Heat) 300-380W (No Heat) 3.8 - 4.1 A / 208 - 240 V / 750 - 950 W (Heat) 300-415W (No Heat) 3.8 - 4.1 A / 208 - 277 V / 750 - 950 W (Heat) 300-415 W (No Heat) 4.0 A / 230 V / 920 W (Heat) 415 W (No Heat)	10 A / 110 V / 1000 W 8.33 A / 120 V / 1000 W 4.55 A / 220 V / 1000 W 4.17 A / 240 V / 1000 W
AIR VELOCITY	13,000 - 20,000 LFM	11,000 - 18,000 LFM @ Air Outlet min/max	36,960 LFM at apertures
FLOW RATE	42 - 63 CFM	27 - 44 CFM	Up to 42.38 CFM
HEATING ELEMENT	Yes (Faster Drying, Increased User Comfort)	Yes (Faster Drying, Increased User Comfort)	No
COUNTRY OF ORIGIN	Made in U.S.A. Certified®	Made in U.S.A. Certified®	Malaysia
CUSTOM COVERS	Yes	Yes	No
ADJUSTABLE SOUND	Yes (65 - 75 dBA <sup>2</sup> )	Yes (69 - 73 dBA average min/max)	No (79 dB)
ADJUSTABLE SPEED	Yes	Yes	No
ADJUSTABLE HEAT	Yes (OFF to Hi 72°F - 135°F)	Yes (OFF to Hi 92°F - 135°F Average @ Air Outlet)	No
ELECTROSTATIC HEPA (eHEPA®) FILTRATION <sup>3</sup>	Yes (HEPA <sup>3</sup> & Pre-Filter)	Yes (HEPA & Pre-Filter)	No (Standard HEPA)
WELL CREDITS	Yes	Yes	Yes
WARRANTY	7 Year Limited	5 Year Limited (Motor and Parts)	5 Year Limited

LEED V4 RATING SYSTEMS <sup>4</sup>			
BD+C AND ID+C	4	5	2
O+M	9	4	7

<sup>1</sup>Dry time and energy use testing performed by SGS International on standard XLERATOR and ThinAir Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers. <sup>2</sup>dBA is an expression of the relative loudness of sounds in air as perceived by the human ear. <sup>3</sup>Optional Electrostatic HEPA (eHEPA®) Filtration System now available for all Excel Hand Dryers will add cost depending on model and quantity. <sup>4</sup>LEED contribution information from publicly available data by Dyson.



# TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

JAN 2026

EDC26028.219.1