

HAND DRYER COMPARISON

XLERATOR®/XLERATOReco® VS. Dyson Airblade V



COMPANY	EXCEL DRYER	EXCEL DRYER	DYSON
SERIES	XLERATOR	XLERATOReco	Airblade V
MODEL	XL-BW, W, GR, SP, SI, C, SB, SB-SI	XL-BW, W, GR, SP, SI, C, SB, SB-SI-ECO	HU02
ONLINE PRICING	\$535 - \$1,110	\$505 - \$1,070	\$949



Smart EPD® verifies Environmental Product Declarations (EPDs) for consistency with the LCA and conformance with global Product Category Rules (PCR) for hand dryers. UL Environment published the first global PCR for hand dryers. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in Environmental Product Declarations, enabling specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.



PCR TESTED	Yes	Yes	No
DRY TIME¹	8 sec	10 sec	12 sec
ENERGY PER USE¹	3.7 Wh	1.7 Wh	N/A
EPD CERTIFIED	Yes	Yes	No
HPD CERTIFIED	Yes	Yes	No

COVER MATERIAL	Thermoset BMC-Composite, Zinc Die-Cast, Stainless Steel	Thermoset BMC-Composite, Zinc Die-Cast, Stainless Steel	Polycarbonate ABS Plastic
FINISH	White, Textured Graphite, Chrome, Custom Special Paint, Special Image, Brushed Stainless, Brushed Stainless Special Image	White, Textured Graphite, Chrome, Custom Special Paint, Special Image, Brushed Stainless, Brushed Stainless Special Image	White, Sprayed Nickel
AMPS/VOLTS/WATTS	11.3 - 12.2 A / 110 - 120 V / 1240 - 1450 W 5.6 - 6.2 A / 208 - 277 V / 1160 - 1490 W 6.1 A / 230 V / 1410 W	4.3 - 4.5 A / 110 - 120 V / 460 - 530 W 2 - 2.2 A / 208 - 277 V / 425 - 500 W 2.2 A / 230 V / 500 W	10 A / 110 V / 1000 W 8.33 A / 120 V / 1000 W 4.55 A / 220 V / 1000 W 4.17 A / 240 V / 1000 W
AIR VELOCITY	13,000 - 20,000 LFM	13,000 - 20,000 LFM	36,960 LFM at apertures
FLOW RATE	42 - 63 CFM	42 - 65 CFM	Up to 42.38 CFM
HEATING ELEMENT	Yes (Faster Drying)	No	No
COUNTRY OF ORIGIN	Made in U.S.A. Certified®	Made in U.S.A. Certified®	Malaysia
CUSTOM COVERS	Yes	Yes	No
ADJUSTABLE SOUND	Yes (65 - 75 dBA²)	Yes (65 - 75 dB)	No (79 dB)
ADJUSTABLE SPEED	Yes	Yes	No
ADJUSTABLE HEAT	Yes (OFF to Hi 72°F - 135°F)	No	No
ELECTROSTATIC HEPA (eHEPA®) FILTRATION³	Yes (HEPA³ & Pre-Filter)	Yes (HEPA & Pre-Filter)	No (Standard HEPA)
WELL CREDITS	Yes	Yes	Yes
WARRANTY	7 Year Limited	7 Year Limited	5 Year Limited

LEED V4 RATING SYSTEMS⁴			
BD+C AND ID+C	4	4	2
O+M	9	9	7

¹Dry time and energy use testing performed by SGS International on standard XLERATOR and ThinAir Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers. ²dBA is an expression of the relative loudness of sounds in air as perceived by the human ear. ³Optional Electrostatic HEPA (eHEPA®) Filtration System now available for all Excel Hand Dryers will add cost depending on model and quantity. ⁴LEED contribution information from publicly available data.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRYER.COM

JAN 2026

EDC26028.217.1